

**2018 CSBC / 2018 CSFSC Part III. Chapter #10. Means of Egress.**  
**Table of Contents. Based on the 2015 IBC and the 2015 IFC.**

**October 23, 2018**

**Section 1001. Administration.** See Section 107.2.3 for Egress Drawing Requirements.

**Section 1002 Definitions.** See Chapter 2. Such as:

- Accessible Means of Egress
- Common Path of Travel
- Corridor
- Exit
- Floor Area, Gross
- Floor Area, Net
- Means of Egress
- Public Way.

**Section 1003. General Means of Egress.**

- 1003.2 Ceiling Height. 7'6"
- 1003.3 Protruding Objects
  - 1003.3.1 Headroom
  - 1003.3.2 Post Mounted Objects.
  - 1003.3.3 Horizontal Projections.
  - 1003.3.4 Clear Width
- 1003.4 Floor Surface
- 1003.5 Elevation Change. 12". Including Stairs with One or Two Risers.
- 1003.6 Means of Egress Continuity. The required capacity of a means of egress system shall not be diminished along the path of egress travel.
- 1003.7 Elevators. Accessible Means of Egress. 1009.4
- 1003.8 Security Device. Ct. Amd.

**Section 1004. Occupant Load.**

- 1004.1. Design Occupant Load.
  - 1004.1.1 Cumulative Occupant Loads. Intervening Spaces. Adjacent Levels.
  - 1004.1.2 Areas without fixed seating. Table 1004.1.2. Ct. Amd. Removed Exception
- 1004.2 Increased Occupant Load.
- 1004.3 Posting of Occupant Load. Assembly Occupancy.
- 1004.4 Fixed Seating.
- 1004.5 Outdoor Areas.
- 1004.6 Multiple Occupancies.

**Section 1005. Means of Egress Sizing**

- 1005.1 General. See Means of Egress for Assembly. Section 1029.
- 1005.2 Minimum Width Based on Component.
- 1005.3 Required Capacity Based on Occupant Load.

- 1005.3.1 Stairways. Egress Capacity Factor of 0.3 inch per occupant. Ct. Amd.
  - 1005.3.2 Other Egress Components. Egress Capacity Factor of 0.2 inch per occupant. Ct. Amd.
  - 1005.4 Continuity. Capacity of means of egress required not be reduced.
  - 1005.5 Distribution of Egress Capacity. Loss of any one exit, not to reduce capacity below 50% of the required capacity.
  - 1005.6 Egress Convergence. Two Stories to an intermediate level.
  - 1005.7 Encroachment. Door Swing, Handrails and Protruding Objects.
- Section 1003.3

**Section 1006. Number of Exits and Exit Access Doorways.**

- 1006.1 General. Number of Exits. Section 1006.2 for Spaces with one means of egress. Section 1006.3 for Stories with one means of egress. Ct. Amd.
- 1006.2. Egress from Spaces including Mezzanines
  - 1006.2.1 Egress based on occupant load and common path of egress travel distance. Table 1006.2.1. Spaces with One Exit or Exit Access Doorway.
    - 1006.2.1.1 Three or more exits or exit access doorways. Greater than 500 persons.
    - 1006.2.2 Egress based on use.
      - 1006.2.2.1 Boiler and Furnace Rooms. Over 500 s.f. and 400,000 BTU.
      - 1006.2.2.2 Refrigeration Machinery Rooms. Over 1,000 s.f.
      - 1006.2.2.3 Refrigerated Rooms or Spaces. Over 1,000 s.f.
      - 1006.2.2.4 Day Care Means of Egress. Ct. Amd.
      - 1006.2.2.5 Vehicular Ramps.
  - 1006.3 Egress from Stories or Occupied Roofs.
    - 1006.3.1 Egress Based on Occupant Load. Table 1006.3.1. Number of Exits.
    - 1006.3.2 Single Exits. Permitted from any Story. Stories with One Exit.
      - 1006.3.2(1) Table. Stories with One Exit. R-2 Occupancy.
      - 1006.3.2(2) Table. Stores with One Exit. Other an R-2 Occupancy.
        - 1006.3.2.1 Mixed Occupancies.

**Section 1007. Exit and Exit Access Doorway Configuration**

- 1007.1 General. Exits to be separated from each other.
  - 1007.1.1 Two Exits or Exit Access Doorways. Remoteness. 1/2, 1/3 or measure along one-hour rated corridor.
    - 1007.1.1.1 Measurement Point.
  - 1007.1.2 Three or More Exits or Exit Access Doorways. Remoteness.
  - 1007.1.3 Remoteness of Exit Access Stairways.
    - 1007.1.3.1 Three or More Exit Access Stairways.

**Section 1008. Means of Egress Illumination.** (Exit Signage. Section 1013).

- 1008.1 Means of Egress Illumination.
- 1008.2 Illumination Required. When Occupied. Ct. Amd.
  - 1008.2.1 Illumination Level Under Normal Power. One Foot-candle.
  - 1008.2.2 Exit Discharge. Group I-2. Section 1010.1.6
  - 1008.2.3 Arrangement of Illumination. Failure of a single lamp. Ct. Amd.

- 1008.3 Emergency Power for Illumination
  - 1008.3.1 General. Rooms and Spaces. Aisles, Corridors and Stairways.
  - 1008.3.2 Buildings. Stairways, Exit Passageways, Vestibules and Exterior Landings. Section 1010.1.6
  - 1008.3.3 Rooms and Spaces. Electrical Rooms, Fire Command Centers, Fire Pump Rooms, Generator Rooms and Public Toilets > 300 s.f. Ct. Amd.
  - 1008.3.4 Duration. 90-minutes
  - 1008.3.5 Illumination Level Under Emergency Power. One Foot-candle.
  - 1008.3.6 Activation. Emergency Illumination. Utility, Circuit Breaker or Switch.

**Section 1009. Accessible Means of Egress.**

- 1009.1 Accessible Means of Egress Required. At least one accessible means of egress. If more than one means of egress, at least two accessible means of egress. Not required in existing buildings.
- 1009.2 Continuity and Components.
  - 1009.2.1 Elevator Required. Five Storeys. Elevator with standby power to be provided. Section 1009.4
- 1009.3 Stairways. 48” Minimum between handrails and area of refuge. Exception for automatic sprinkler system.
- 1009.4 Elevators. Standby power requirements. Chapter #27 and Section 3003.
- 1009.5 Platform Lifts. Accessible route. Section 1109.8. Chapter #27.
- 1009.6 Area of Refuge
  - 1009.6.1 Travel Distance. Section 1017.1
  - 1009.6.2 Stairway or Elevator Access.
  - 1009.6.3 Size
  - 1009.6.4 Separation. Smoke Barrier Section 709 or Stair Enclosure Section 1023
  - 1009.6.5 Two-Way Communication at area of refuge. Section 1009.8.1 and 1009.8.2.
- 1009.7 Exterior areas for Assisted Rescue.
  - 1009.7.1 Size.
  - 1009.7.2 Separation. Interior of the building.
  - 1009.7.3 Openness
  - 1009.7.4. Stairways. Width of Stairs.
- 1009.8 Two-Way Communications. Elevator Landing.
  - 1009.8.1 System Requirements.
  - 1009.8.2 Directions. Two-Way Communication System Signage.
- 1009.9 Signage. Area of Refuge. Exterior Area of Assisted Rescue.
- 1009.10 Directional Signage. Accessible Means of Egress. Elevator Landings
- 1009.11 Instructions. Area of Refuge and Exterior Areas of Assisted Rescue. Use of Area.

**Section 1010. Doors, Gates and Turnstiles.**

- 1010.1 Doors.
  - 1010.1.1 Size of Doors.
    - 1010.1.1.1 Projections into Clear Width
    - 1010.1.1.2 Bed and Breakfast Establishments. Ct. Amd.

- 1010.1.2 Door Swing. Side hinged swinging. See 1005.7.1 Door Encroachment.
- 1010.1.2.1 Direction of Swing. Ct. Amd.
- 1010.1.3 Door Opening Force
- 1010.1.3.1. Location of Applied Forces.
- 1010.1.4 Special Doors
- 1010.1.4.1 Revolving Doors.
- 1010.1.4.1.1. Egress Component for Revolving Doors.
- 1010.1.4.1.2. Other Than Egress Component for Revolving Doors.
- 1010.1.4.2 Power Operated Doors.
- 1010.1.4.3 Special Purpose Horizontal Sliding Doors.
- 1010.1.4.4 Security Grilles
- 1010.1.5 Floor Elevation. Same elevation on each side of the door.
- 1010.1.6 Landings at Doors. Width of landing. Door fully open not reduce by more than 7". Door swing, one half the required width. Landing size.
- 1010.1.7 Thresholds. Exception: Threshold Height. ¾" in Dwelling Units.
- 1010.1.8 Door Arrangement. 48" between two doors in series.
- 1010.1.9 Door Operation. Without use of key or special knowledge.
- 1010.1.9.1 Door Hardware. Lever Hardware.
- 1010.1.9.2 Door Hardware Height. Pool Exception.
- 1010.1.9.3 Door Locks and Latches. Door to remain unlocked when building is occupied. Exceptions provided.
- 1010.1.9.4 Door Bolt Locks. Flush bolts or surface bolts. Exceptions provided.
- 1010.1.9.5 Door Unlatching. One operation.
- 1010.1.9.5.1 Closet and Bathroom Doors. R-4, I-2, I-4. Ct. Amd.
- 1010.1.9.6 Controlled Egress Doors in Groups I-1 and I-2. Special Locking.
- 1010.1.9.7 Delayed Egress Locks. Not for Groups A, E and H.
- 1010.1.9.8 Sensor Release of Electrically Locked Egress Doors.
- 1010.1.9.9 Electromagnetically Locked Egress Doors.
- 1010.1.9.10 Locking Arrangements in Correctional Facilities.
- 1010.1.9.11 Stairway Doors. Openable from both sides. Re-Entry.
- 1010.1.10 Panic and Fire Exit Hardware. Group H. Groups A & E. 50 or more. Electrical Rooms 1,200 Amps or greater.
- 1010.2 Gates
- 1010.2.1 Stadiums. Gates.
- 1010.3 Turnstiles
- 1010.3.1 High Turnstile.
- 1010.3.2 Additional Door

## **Section 1011. Stairways**

- 1011.1 General
- 1011.2 Width and Capacity.
- 1011.3 Headroom.
- 1011.4 Walkline. Winder Stairs.
- 1011.5 Stair Reads and Risers.
- 1011.5.1 Dimension Reference Surfaces.
- 1011.5.2 Riser Height and Tread Depth. Ct. Amd.

- 1011.5.3 Winder Treads. Dwelling Units. Ct. Amd.
- 1011.5.4 Dimensional Uniformity. 3/8" (.374) difference.
  - 1011.5.4.1 Nonuniform Height Risers. Public Way.
- 1011.5.5 Nosing and Riser Profile.
- 1011.6 Stairway Landings.
- 1011.7 Stairway Construction.
  - 1011.7.1 Stairway Walking Surface. Slope of surface. Solid treads and risers.
  - 1011.7.2 Stairway Outdoor Conditions. Snow Conditions. Ct. Amd. Mod.
  - 1011.7.3 Enclosures Under Interior Stairways.
  - 11.7.4 Enclosures Under Exterior Stairways.
- 1011.8 Stairway Vertical Rise. 12 feet.
- 1011.9 Curved Stairways
- 1011.10 Spiral Stairways
- 1011.11 Handrails. Section 1003.5. Section 1014. Section 2407 Glass. Ct Amd.
- 1011.12. Stairway to Roof. Four or more stories.
  - 1011.12.1 Stairway to Elevator Equipment.
  - 1011.12.2 Roof Access.
- 1011.13 Guards. Section 1015. Stairways and 10 feet to roof edge.
- 1011.14 Alternating Tread Devices.
  - 1011.14.1 Handrails of Alternating Tread Devices.
  - 1011.14.2 Treads of Alternating Tread Devices.
- 1011.15 Ship Ladders. Access to Unoccupied Roofs.
  - 1011.15.1 Handrails of Ships Ladders
  - 1011.15.2 Treads of Ships Ladders.
- 1011.16 Ladders

**Section 1012. Ramps.**

- 1012.1 Scope
- 1012.2 Slope
- 1012.3 Cross Slope.
- 1012.4 Vertical Rise
- 1012.5 Minimum Dimensions
  - 1012.5.1 Width and Capacity
  - 1012.5.2 Headroom
  - 1012.5.3 Restrictions
- 1012.6 Landings.
  - 1012.6.1 Slope.
  - 1012.6.2 Width
  - 1012.6.3 Length
  - 1012.6.4 Change in Direction
  - 1012.6.5 Doorways
- 1012.7 Ramp Construction.
  - 1012.7.1 Ramp Surface
  - 1012.7.2 Outdoor Conditions.
- 1012.8 Handrails. Rise Greater than 6". Section 1014
- 1012.9 Guards. Section 1015

- 1012.10 Edge Protection.
- 1012.10.1 Curb, Rail, Wall or Barrier
- 1012.10.2 Extended Floor or Ground Surface

**Section 1013. Exit Signs.** (Emergency Lighting Section 1008).

- 1013.1 Where Required.
- 1013.1.1 Accessible Exits. CT Amd.
- 1013.2 Floor Level Exit Signs. R-1, I-2, R-2. Section 1013.1 Ct. Amd.
- 1013.3 Illumination
- 1013.4 Raised Character and Braille Exit Signs.
- 1013.5 Internally Illuminated Exit Signs.
- 1013.6 Externally Illuminated Exit Signs.
- 1013.6.1 Graphics
- 1013.6.2 Exit Sign Illumination
- 1013.6.3 Power Source

**Section 1014. Handrails.**

- 1014.1 Where Required. Section 1011.11 Stairways. Section 1012.8 Ramps.
- 1014.2 Height. 34" to 38".
- 1014.3 Handrail Graspability. Type I
- 1014.3.1 Type I
- 1014.3.2 Type II
- 1014.4 Continuity
- 1014.5 Fittings
- 1014.6 Handrail Extensions.
- 1014.7 Clearance. 1 ½".
- 1014.8 Projections. Limited to 4 ½".
- 1014.9 Intermediate Handrails. Ct. Amd.

**Section 1015. Guards.**

- 1015.1 General
- 1015.2 Where Required.
- 1015.2.1 Glazing. Section 2407. Section 1607.8
- 1015.3 Height. Ct. Amd.
- 1015.4 Opening Limitations. Ct. Amd.
- 1015.5 Screen Porches
- 1015.6 Mechanical Equipment, Systems and Devices. Roof or walking surface.  
See 2015 IMC 304.11
- 1015.7 Roof Access. 10 feet to roof edge.
- 1015.8 Window Openings.
- 1015.8.1 Window Opening Control Devices
- 1015.9 Retaining Walls. Ct. Amd.

**Section 1016. Exit Access.** Travel Distance in Section 1017.

1016.1 General

1016.2 Egress Through Intervening Spaces. Elevator Lobby. Accessory to area. Not high hazard.

1016.2.1 Multiple Tenants. Passing through adjacent space. Exception.

**Section 1017. Exit Access Travel Distance.**

1017.1 General

1017.2 Travel Distance Limitations. Table 1017.2. Exit Access Travel Distance. Ct. Amd.

1017.2.1 Exterior Egress Balcony Increase.

1017.2.2 Group F-1 and S-1 Increase. 400 feet.

1017.3 Measurement.

1017.3.1 Exit Access Stairways and Ramps.

**Section 1018. Aisles.**

1018.1 General

1018.2 Aisles in Assembly Spaces. Section 1029

1018.3 Aisles in Groups B and M. Section 1020.2

1018.4 Aisles Accessways in Group M.

1018.5 Aisles in Other Than Assembly Spaces and Group B and M.

**Section 1019. Exit Access Stairways and Ramps.**

1019.1 General

1019.2 All Occupancies. Stairs within a single story.

1019.3 Occupancies Other than Groups 1-2 and 1-3. Ct. Amd. Limited. Section 713.

1019.4 Group I-2 and I-3 Occupancies. Section 713.

**Section 1020. Corridors.**

1020.1 Construction. Table 1020.1

1020.1.1 Group R-1 Bed and Breakfast Establishments. Ct. Amd.

1020.1 Table. Corridor Fire Resistance Rating. Ct. Amd.

1020.2 Corridor Width. Table 1020.2 Minimum Corridor Width. I-2 Exception.

1020.3 Obstruction. Encroachment. Section 1005.7.

1020.4 Dead Ends. 20 Feet. Exceptions for 50 Feet.

1020.5 Air Movement in Corridors.

1020.5.1 Corridor Ceilings. Air Plenum.

1020.6 Corridor Continuity. Section 1016.2. Elevator Lobby Enclosure.

**Section 1021. Egress Balconies**

Section 1021.1 General

Section 1021.2 Wall Separation

Section 1021.3 Openness

Section 1021.4 Location

**Section 1022 Exits.**

- 1022.1 General. No use that interferes with means of egress. No reduction of protection.
- 1022.2 Exterior Exit Doors.
  - 1022.2.1 Detailed Requirements. Section 1010.1
  - 1022.2.2 Arrangement.
- 1022.3 Mercantile Occupancies. 1/2 of required egress width on one wall. Ct. Amd.

**Section 1023 Interior Exit Stairways and Ramps.** See 712 for Vertical Openings.

- 1023.1 General. No use other than means of egress.
- 1023.2 Construction. One-Hour / Two-Hour. Section 707. Section 711
- 1023.3 Termination.
  - 1023.3.1. Extension. Exit Passageway
- 1023.4 Openings. Exit access from normally occupied spaces.
- 1023.5 Penetrations. Ct. Amd. Security Systems.
- 1023.6 Ventilation
- 1023.7 Interior Exit Stairways and Ramp Exterior Walls. Less than 180\*.
- 1023.8 Discharge Identification. Swing Gate.
- 1023.9 Stairway Identification Signs. Stairway Floor Number Signs. Greater than three floors.
  - 1023.9.1 Signage Requirements
- 1023.10 Elevator Lobby Identification Signs.
- 1023.11 Smokeproof Enclosures and Pressurized Stairways and Ramps. Section 403.5.4, Section 405.7.2. Section 909.20
  - 1023.11.1 Termination and Extension. Exit Passageway.
  - 1023.11.2 Enclosure Access.

**Section 1024 Exit Passageway.**

- 1024.1 Exit Passageway. Means of Egress.
- 1024.2 Width
- 1024.3 Construction. Rating to match stair enclosure. One or Two Hour.
- 1024.4 Termination. Exit Discharge
- 1023.5 Openings. Section 716. Normally occupied spaces.
- 1024.6 Penetrations. Ct. Amd.
- 1024.7 Ventilation.

**Section 1025 Luminous Egress Path Markings**

- 1025.1 General. High-Rise Buildings. Groups A, B, E, I, M & R-1.
- 1025.2 Markings Within Exit Components.
  - 1025.2.1 Steps
  - 1025.2.2 Landings
  - 1025.2.3 Handrails
  - 1025.2.4 Perimeter Demarcation Lines
    - 1025.2.4.1 Floor-mounted Demarcation Lines.
    - 1025.2.4.2 Wall-mounted Demarcation Lines.



- 1025.2.4.3 Transition.
- 1025.2.5 Obstacles.
- 1025.2.6 Doors within the Exit Path
  - 1025.2.6.1 Emergency Exit Symbol
  - 1025.2.6.2 Door Hardware Markings
  - 1025.2.6.3 Door Frame Markings
- 1025.3 Uniformity
- 1024.4 Self Luminous and Photoluminescent.
- 1024.5 Illumination
- 1025.6 Statutory Requirements for Exit Access Corridors. Ct. Amd.  
Occupancy A over 300 persons, B Medical, E, I-1, I-2, R-1 Hotels, R-2  
Dormitories. Newly Constructed Occupancies.
  - 1025.6.1 Size and Location. Ct. Amd.
  - 1025.6.2 Device or System Requirements. Ct. Amd.
  - 1025.6.3 Illumination. Ct. Amd.

**Section 1026 Horizontal Exits.**

- 1026.1 Horizontal Exits.
- 1026.2 Separation. Fire Wall or Fire Barrier. Two-Hour Rated.
- 1026.3 Opening Protectives. Section 716.5.9.3. Doors
- 1026.4 Refuge Area.
  - 1026.4.1 Capacity
  - 1026.4.2. Number of Exits.

**Section 1027 Exterior Exit Stairways and Ramps.**

- 1027.1 Exterior Exit Stairways and Ramps.
- 1027.2 Use in a Means of Egress
- 1027.3 Open Side.
- 1027.4 Side Yards
- 1027.5 Location. 10 feet Separation Distance.
- 1027.6 Exterior Ramps and Stairway Protection. Separation to the interior.  
Less than 180\*.

**Section 1028 Exit Discharge**

- 1028.1 General. 50% on the LED requirements.
- 1028.2 Exit Discharge Width or Capacity
- 1028.3 Exit Discharge Components.
  - 1028.3.1 Remoteness of Exit Discharge. Ct. Amd.
- 1028.4 Egress Courts.
  - 1028.4.1 Width or Capacity
  - 1028.4.2 Construction and Openings
- 1028.5 Access to a Public Way. Safe dispersal area.

## **Section 1029 Assembly.**

- 1029.1 General
  - 1029.1.1 Bleachers. ICC 300 2012
    - 1029.1.1.1 Spaces Under Grandstands and Bleachers. One-Hour Separation
- 1029.2 Assembly Main Exit. Ct. Amd. 2/3 Rule.
- 1029.3 Assembly Other Exits.
- 1029.4 Foyers and Lobbies. Waiting Areas. Clear Path.
- 1029.5 Interior Balcony and Gallery Means of Egress.
- 1029.6 Capacity of Aisle for Assembly.
  - 1029.6.1 Without Smoke Protection.
  - 1029.6.2 Smoke Protected Assembly Seating.
    - 1029.6.2.1 Smoke Control.
    - 1029.6.2.2 Roof Height
    - 1029.6.2.3. Automatic Sprinklers
  - 1029.6.3. Outdoor Smoke-Protected Assembly Seating.
- 1029.7 Travel Distance.
- 1029.8 Common Path of Travel.
  - 1029.8.1 Path Through Adjacent Row.
- 1029.9 Assembly Aisles are Required.
  - 1029.9.1 Minimum Aisle Width.
  - 1029.9.2 Aisle Catchment Areas.
  - 1029.9.3 Converging Aisles.
  - 1029.9.4 Uniform Width and Capacity.
  - 1029.9.5 Dead End Aisles.
  - 1029.9.6 Aisle Measurement
    - 1029.9.6.1 Assembly Aisle Obstructions.
  - 1029.9.7 Stairways Connecting to Stepped Aisles.
  - 1029.9.8 Stairways Connecting to Vomitories.
- 1029.10 Transitions.
  - 1029.10.1. Transitions and Stairways that Maintain Stepped Aisle Riser and Tread Dimensions.
  - 1029.10.2 Transitions to Stairways that do not Maintain Stepped Aisle Riser and Tread Dimensions.
    - 1029.10.2.1 Stairways and Stepped Aisles in a Straight Run.
    - 1029.10.2.2 Stairways and Stepped Aisles that Change Direction.
  - 1029.10.3. Transition Marking
- 1029.11 Construction. Aisles, Stepped Aisles and Ramped Aisles.
  - 1029.11.1 Waling Surface.
  - 1029.11.2 Outdoor Conditions.
- 1029.12 Aisle Accessways. Seating at Tables.
  - 1029.12.1 Seating at Tables.
    - 1029.12.1.1 Aisle Accessway Capacity and Width for Seating at Tables.
    - 1029.12.1.2 Seating at Table Aisle Accessway Length.
  - 1029.12.2 Clear Width of Aisle Accessway Serving Seating in Rows.
    - 1029.12.2.1 Dual Access.
    - 1029.12.2.2 Single Access.

- 1029.13 Assembly Aisle Walking Surfaces.
  - 1029.13.1 Ramped Aisles
    - 1029.13.1.1 Cross Slope
    - 1029.13.1.2 Landings
    - 1029.13.1.3 Edge Protection
  - 1029.13.2 Stepped Aisles
    - 1029.13.2.1 Treads
    - 1029.13.2.2 Risers
      - 1029.13.2.2.1 Construction Tolerances.
    - 1029.13.2.3 Tread Contrasting Marking Stripe
    - 1029.13.2.4 Nosing and Profile. Section 1011.5.5 through 1011.5.5.3.
- 1029.14 Seat Stability. 200 Seat Rule.
- 1029.15 Handrails. Section 1014.
  - 1029.15.1 Discontinuous Handrails
  - 1029.15.2 Handrail Termination.
  - 1029.15.3 Mid-Aisle Termination.
  - 1029.15.3 Rails. Lower Handrail.
- 1029.16 Assembly Guards.
  - 1029.16.1 Perimeter Guards
  - 1029.16.2 Cross Aisles
  - 1029.16.3 Sightline Constrained Guard Heights.
  - 1029.16.4 Guards at the End of Aisles.

**Section 1030 Emergency Escape and Rescue**

- 1030.1 General. R-2 Units as per Table 1016.3.2(1) and 1016.3.2(2) and R-3. Ct. Amd.
  - 1030.1.1 Operations Constraints and Opening Control Devices. Ct. Amd.
  - 1030.1.2 Group E Occupancies. Ct. Amd.
  - 1030.1.3 Group I-4 Occupancies. Ct. Amd.
- 1030.2 Minimum Size.
  - 1030.2.1 Minimum Dimensions. Ct. Amd.
- 1030.3 Maximum Height From Floor. Ct. Amd.
- 1030.4 Operational Constraints
- 1030.5 Window Wells.
  - 1030.5.1 Minimum Size.
  - 1030.5.2 Ladders or Steps.

**Section 1031 Maintenance of the Means of Egress. 2015 IFC.**

- 1031.1 General
- 1031.2 Reliability.
  - 1031.2.1 Security Devices and Egress Locks
- 1031.3 Obstructions
  - 1031.3.1 Group I-2. Section 1020.2
- 1031.4 Exit Signs. Section 1013.
- 1031.5 Nonexit Identification.
- 1031.6 Finishes, Furnishings and Decorations.

1031.7 Emergency Escape and Rescue Openings.  
1031.8 Inspections, Testing and Maintenance.  
1031.9 Floor Identification Signs. Section 1023.9

Douglas L. Golden  
Bruce J. Spiewak, AIA Consulting Architect, LLC  
375 Morgan Lane. Unit 405  
West Haven, Conn. 06516-4159  
October 23, 2018